



MANUFACTURED IN IRELAND

[www.csc.ie](http://www.csc.ie) [sales@csc.ie](mailto:sales@csc.ie)

Phone: 353 (0)1 835 1311

Fax : 353 (0)1 835 1580

CHEMICAL STORAGE

SOLVENT STORAGE

## Tall Solvent Storage

Our tall solvent units provide safe and approved storage of hazardous materials in work rooms. Certified to both EN 14470-1 and EN 14727 ratings, these units come standard with a 5yr warranty. We carry a wide variety of models and sizes; the models below are our most popular.



### Key Features:

- Corrosion-protected assembly of safety elements
- Air damped door closing, door open arrest system (optional),
- GS-approved with 50,000 non-wearing open-close cycles
- Integrated air ducts ready for connection (NW75) to a technical exhaust system
- Protection against unauthorised use lockable doors with cylinder lock
- Optional Metal-free interior equipment
- Ideal for the storage of flammable, aggressive hazardous substances
- Tray shelves with chemical resistant surface lamination and removable sump made of PE
- Bottom collecting sump made of PE Drawers
- High storage capacity
- Furnace tested (type test) in accordance with EN 14470-1
- Fire resistance 90 minutes
- GS approval, CE conformity

## Standard Configurations

Model	S90.196.060	S90.196.120
External Dimensions (WxDxH)	596x616x1968	1196x616x1968
Working Internal (WxDxH)	450x524x1742	1050x524x1742
GS Approval	CE Conformity	CE Conformity
Extract Air Connection	75NW	75NW
Furnace tested	EN 14470-1	EN 14470-1
Air Changes 10 Times	4.1 m <sup>3</sup> /h	9.6 (0.9) m <sup>3</sup> /h
Pressure Drop	Pa <5	Pa <5
Warranty	5 Years	5 Years
Maximum Load	600kg	600kg
Distributed Load	893 (kg/m <sup>2</sup> )	628 (kg/m <sup>2</sup> )